

Product	Sinopec JUSTAR J700F SUPER 5W-30 Engine Oil
Summary	Product description Sinopec JUSTAR J700F SUPER 5W-30 Engine Oil formulated with highly refined base oils and premium additive system, providing good protection for vehicles with DPF and TWC in high performance cars and light duty van and trucks with diesel or petrol engines. The oil can meet VW50400/50700 and API SN requirement, functionally meet ACEA C3 specification.

Applications

Sinopec JUSTAR J700F SUPER 5W-30 Engine Oil is suitable for use in:

- Petrol or diesel engines requiring oils of VW50400/50700 or API SN.
- High performance car and light duty van/trucks with DPF and TWC
- Both new and conventional American and Japan, especially European high performance engines or vehicles, like VW, Volvo, BMW, Benz and Ford and etc.

Features and benefits

- Extending the life of vehicles with DPF and TWC, providing comprehensive premium protection for engines especially for high performance petrol and diesel engines.
- Balanced start-up performance in low temperature and strong oil film lubricating properties in high temperature and high speed, usable in all seasons.
- Excellent anti-wear performance, reducing engine wear effectively to extend engine life.
- Lower viscosity to ensure better fuel economy.

Product Data Sheet

Typical data

Sinopec JUSTAR J700F SUPER 5W-30 Engine Oil	
SAE grade	5W-30
Kinematic Viscosity@ 100°C, cSt, ASTM D 445	12.02
CCS (-35°C) , mPa • s	6090
MRV (-40°C) , mPa • s	17700
TBN (mg KOH/g)	8.92

These data are given as an indication of typical values, not exact specifications.

Industry and OEM specifications

Sinopec JUSTAR J700F SUPER 5W-30 Engine Oil meets the performance requirements of the following industry specifications:	
API Specifications	SN
ACEA Specifications	C3(functionally)
OEM Specifications	VW 50400/50700

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2017

© Sinopec 2017